


Frequently Asked Questions (FAQ)



FriendlyNET 10/100 CardBus

Frequently Asked Questions (FAQ)



Q: What is the Hot-Swap function :

A: The Hot-Swap function which allows the adapter to be removed and re-inserted without reloading the driver.

Q: What is the Hot-Insert function :

A: The Hot-Insert function which allows the adapter to be inserted when Network Operating System is ready.

Q: What have the notebooks been tested for the adapter ?

A: We test the adapter on the following notebooks.
Thes on other notebooks is in progress.

Notebook	CardBus Controller
1) IBM ThinkPad 315ED	TI PCI-1131
2) COMPAQ ARMADA 1598DMT	TI PCI-1131
3) TOSHIBA Satellite 300CDT	ToPIC95
4) Acer EXTENSA 711TE	TI 1250
5) Compal TS30G12	Cirrus CL-PD6832

Q: How about the driver support for Microsoft Windows NT 4.0 ?

A: For Windows NT 4.0 system, since the system do not have the native CardBus adapter support, please refer to the readme file \TXT\MSOFT\NT40.TXT for details of driver installation.

Q: How about the driver support for Microsoft Windows 95 series ?

A: The driver currently works under Windows 95 OSR2 or later version. Please upgrade to Windows 95 OSR2 or later version if your system is an older version.

Microsoft Windows 95, versions 950 and 950a, do not have the plug-and-play support for the CardBus adapters.

Starting from Windows 95 version 950B (OSR2), plug-and-play for CardBus adapters is included.