



## Asanté's 12 and 24-port 10/100 Stackable Hubs with Optional Management Module...Delivering the Power of Fast Ethernet to the Desktop

### NetStacker II Stackable 10/100 Hubs



#### Designed for Maximum Flexibility with Expansion Modules and Easy Migration to a Managed Environment

- Asanté's NetStacker™ Dual-speed Stackable Hubs allow small and larger-sized businesses to implement departmental networks and access network resources at speeds up to 100Mbps, with a design that is plug-and-play ready, cost-effective and expandable.

#### Performance and Flexibility

- Asanté's NetStacker 12 and 24-port dual-speed stackable hubs provide the option of 10Mbps or 100Mbps operation, for connecting network devices such as PCs, Macintosh computers, workstations, and network printers to a Fast Ethernet network.
- NetStacker II Hubs include an internal bridge module allowing simultaneous transmission between 10Mbps and 100Mbps connections.
- NWay auto-negotiation makes installation and configuration easy by automatically detecting and configuring 10Mbps or 100Mbps.
- Supports up to eight unmanaged 12 or 24-port stacked units for up to 192 ports, and includes one standard MII slot on each unit for 100Base-FX connectivity options.
- Also includes an easy to use push-button uplink option for port 12 of each NetStacker unit.

Expandable

#### Management

- For simple migration to a managed network, NetStacker II's optional management module offers full SNMP read/write configuration and traffic analysis, as well as easy to use browser-based management from anywhere on your network.
- Add the management module to any unit in the stack to manage the entire stack.
- LED lights provide at-a-glance management displaying power, port activity, 10/100Mbps operation, link and collision status.

Optional Management

#### Ease of Installation and Use

- The plug-and-play design of the NetStacker II Hubs make set-up and connection to your PCs, Macintoshes, workstations, (including UNIX) and servers easy—simply plug it in and you're up and running in no time.
- Asanté's NetStacker Hubs support all popular network operating systems including AppleShare, AppleTalk, Novell NetWare, TCP/IP, and other NDIS and ODI-compliant operating systems.

Free Technical Support

#### Technical Support

- Asanté offers free technical support by calling our toll-free technical support line from 7 AM - 6 PM (MST) Monday through Friday, via Email, our Web site, or our 24-hour BBS.

#### Warranty

- Asanté stands behind the NetStacker II by providing a limited 5 year warranty, without the purchase of an extended warranty contract.

#### NetStacker II Hubs Add Up to Value

- With the NetStacker's II, Asanté provides affordable 10/100Mbps connectivity to the desktop to enable your business to benefit from Fast Ethernet technology today with the flexibility of stackable expansion and management modules for the future. Combine this with free technical support, and a plug-and-play design for a solution that meets the needs of your users and your budget.

Limited Five Year  
Warranty  
Asanté stands behind  
NetStacker II  
Dual-speed Hubs  
by providing a  
limited five year  
warranty,  
without the purchase  
of an extended  
warranty contract.

Free Technical Support  
Asanté provides free  
telephone support  
7AM to 6PM (MST)  
as well as 24-hour  
BBS and World Wide  
Web support.

## SPECIFICATIONS

Network Operating Systems Supported:	AppleShare, AppleTalk, Novell NetWare, TCP/IP, and other NDIS and ODI-compliant operating systems		
LEDs:	Power, collision, link status, and 10Mbps and 100Mbps operation		
Connector:	RJ-45 (female)		
Maximum Cable Distances Unshielded Twisted Pair:	328' maximum (100 m), 24 AWGUTP		
Dimensions:			
12-port:	17.3 x 10.1 x 1.8 (439.4 x 256.5 x 44.5 mm)		
24-port:	17.3 x 10.1 x 1.8 (439.4 x 256.5 x 44.5 mm)		
Weight:			
12-port:	6.8 lbs (3.1 kg)		
24-port:	7.4lbs (3.4 kg)		
Environmental Conditions:			
Temperature:	Operating: 0° to 40° C	Storage: -20° to 70° C	
Humidity:	Operating: 10 to 90% RH	Storage: 5 to 90% RH	
Power Supply:			
Input:	100-240 Vac		
Internal Universal ac Input:	50/60 Hz		
Standards Compliance:	IEEE 802.3 Ethernet specification (10Base-T), IEEE 802.3u (100Base-TX)		
Safety:	CUL (UL and CSA) LVD		
Emissions:	FCC Class A, CE, VCCI 1		
Support:	Limited Five Year Warranty • Free Technical Support • World Wide Web • 24-hour Commercial Online BBS		

## ORDERING INFORMATION

Name	Description	Asanté Part # *
<b>NetStacker II Stackable 10/100 Hubs:</b>		
NS2012 Hub (12-port)	12 10/100Mbps NWay auto-negotiating ports (RJ-45), one MII option slot, stack in/stack out ports, management option slot	99-00532-01
NS2024 Hub (24-port)	24 10/100Mbps NWay auto-negotiating ports (RJ-45), one MII option slot, stack in/stack out ports, management option slot	99-00533-01
NS2000M Module	Management module for 12 or 24 port units	99-00534-01
MII Module	100FX Module for fiber uplink	99-00527-01

\* For international specific part numbers, please refer to the Asanté price list.

Asanté Technologies, Inc. • 821 Fox Lane, San Jose, CA 95131 U.S.A. • T: 408.435.8388, 800.662.9686 F: 408.432.7511;  
Sales Email: sales@asante.com • Tech Support Email: support@asante.com • Web Site: www.asante.com • Asanté-NASDAQ: ASNT.  
Copyright©1999 Asanté Technologies, Inc. All brand names and products are trademarks or registered trademarks of their respective holders.  
All features and specifications subject to change without notice.  
06-00508-00. 5/99



Free telephone support and 24-hour BBS.  
Call our support line at (800) 566-6680 or visit [www.asante.com](http://www.asante.com) for more information.